

Quality Trade 2005, SL
Pol. Ind. IP 7 Avda. de la Diputació 15
46890 Agullent (Valencia)
Tel. 962 36 93 82
info@qualitytrade.es



FICHA TÉCNICA / DATA SHEET

DAMASCO			
COMPOSITION / COMPOSICIÓN		100% PU	
PESO / WEIGHT		385 g/m² ± 3%	
WIDTH / ANCHO		140 CM	
FORRO / BACKING		80% PES 12% COT	
FASTNESS TO RUBBING / SOLIDEZ AL FROTAMIENTO 105X12:2001/COR 2002	ISO	DRY	4-5
		WET	4-5
FASTNESS TO LIGHT / SOLIDEZ A LA LUZ			
GRADE		03-abr	
Iso 105 B02:2014/Xenon-Arc Lamp			
ABRASION RESISTANCE / RESISTENCIA A LA ABRASIÓN			
ISO54720-2:2003, MÉTODO 1, TEST DE MARTINDALE; 12kPa		> 30 000 CYCLES	
TENSILE STRENGTH / RESISTENCIA A LA TRACCIÓN D41 1029 50 N	LONG	1.32 %	
	CROSS	7.29 %	
ELONGATION RATE / TASA DE ALARGAMIENTO Norm NES0154SEC19 FORCE 50N	LONG	≥ 3%	
	CROSS	≥ 21%	
TEAR STRENGHT / RESISTENCIA AL DESGARRO ISO13937-2:2000/D41 1126	LONG	6.851 daN ± 10%	
	CROSS	2.335 daN ± 10%	
FIRE RESISTANCE / RESISTENCIA AL FUEGO EN 597-1 & EN 597-2		PASS	PASS