

Quality Trade 2005, SL

Pol. Ind. IP 7 Avda. de la Diputació 15

46890 Agullent (Valencia)

Tel. 962 36 93 82

info@qualitytrade.es*FICHA TÉCNICA / DATA SHEET***DOTS**

COMPOSITION / COMPOSICIÓN		100% PVC
ROLL LENGHT / LONGITUD DEL ROLLO		AROUND / APROX. 40 MTS
WIDTH / ANCHO		142 ± 2 CM
USABLE WIDTH / ANCHO UTILIZABLE		140 ± 2 CM
WEIGHT IN M ² / PESO EN M ²		681 g/m ² ± 5%
FORRO / BACKING		CHEMICAL FIBER OR PES
FASTNESS TO RUBBING / SOLIDEZ AL FROTAMIENTO	DRY	4-5
<i>ISO 105x12:2001/COR 2002</i>	WET	3-4
FASTNESS TO LIGHT / SOLIDEZ A LA LUZ	GRADE	3/4
<i>ISO 105 B02:1994/Amd 1:1998+Amd2:200</i>		
TENSILE STRENGTH / RESISTENCIA A LA TRACCIÓN	LONG	189 daN ± 5%
<i>ISO 13934-1:2013/D41 1029</i>	CROSS	90 daN ± 5%
ELONGATION AT BREAK / ELONGACIÓN DE ROTURA	LONG	≥ 69%
<i>ISO 13934-1:2013</i>	CROSS	177,50%
TEAR STRENGHT / RESISTENCIA AL DESGARRO	LONG	8.7 daN ± 10%
<i>ISO13937-2:2000/D41 1126</i>	CROSS	18.3 daN ± 10%