

Quality Trade 2005, SL

Pol. Ind. IP 7 Avda. de la Diputació 15

46890 Agullent (Valencia)

Tel. 962 36 93 82

info@qualitytrade.es*FICHA TÉCNICA / DATA SHEET***ECOPIEL**

COMPOSITION / COMPOSICIÓN		100% PVC
ROLL LENGHT / LONGITUD DEL ROLLO		AROUND / APROX. 40 MTS
WIDTH / ANCHO		142 ± 2 CM
USABLE WIDTH / ANCHO UTILIZABLE		140 ± 2 CM
WEIGHT IN M ² / PESO EN M ²		560 g/m ² ± 5%
THICKNESS / ESPESOR		0,80 mm
FORRO / BACKING		KNIT 100% PES
FASTNESS TO RUBBING / SOLIDEZ AL FROTAMIENTO	DRY	4-5
	WET	4-5
<i>FASTNESS TO LIGHT / SOLIDEZ A LA LUZ</i>		
	<i>GRADE</i>	> 5
<i>ISO 105 B02:1994/Amd 1:1998+Amd2:200</i>		
ABRASION RESISTANCE / RESISTENCIA A LA ABRASIÓN		≥ 50,000 CYCLES
<i>ISO 12947-2:1998</i>		PASS / NO DAMAGE
TENSILE STRENGTH / RESISTENCIA A LA TRACCIÓN	LONG	322 N/5CM
	CROSS	170 N/5CM
<i>ISO 13934-1:2013/D41 1029</i>		
ELONGATION AT BREAK / RESISTENCIA A LA TRACCIÓN	LONG	≥ 39%
	CROSS	≥ 210%
<i>ISO 13934-1:2013</i>		
TEAR STRENGHT / RESISTENCIA AL DESGARRO	LONG	50N
	CROSS	29N
<i>ISO13937-2:2000/D41 1126</i>		
FIRE RESISTANCE / RESISTENCIA AL FUEGO	PASS	PASS
<i>EN 597-1 & EN 597-2</i>		